

EMI Inductors Look Up Table for Thru Hole

Submitted by billnbdadmin on Thu, 09/26/2013 - 13:30

Size	Max. Height A	Max Diameter B	Belt Circle C	Standoff	Terminal Diameter	MFG Insert
1	0.280 (7.11)	0.410 (10.41)	0.260 (6.6)	0.160 (4.06)	0.012 (0.31)	
2	0.340 (8.63)	0.500 (12.7)	0.350 (8.89)	0.250 (6.35)	0.012 (0.31)	
3	0.415 (10.54)	0.630 (16.0)	0.440 (11.17)	0.340 (8.64)	0.016 (0.41)	
4	0.500 (12.7)	0.800 (20.32)	0.560 (14.22)	0.460 (11.68)	0.016 (0.41)	2-56 UNC 6 Threads Min
5	0.650 (16.51)	0.950 (24.13)	0.670 (17.0)	0.570 (14.48)	0.020 (0.51)	2-56 UNC 6 Threads Min
6	0.745 (18.92)	1.125 (28.57)	0.800 (20.32)	0.700 (17.78)	0.020 (0.51)	2-56 UNC 6 Threads Min

Product type:

- [EMI Inductors](#)

Product Sub-type:

- [Thru Hole](#)