

80534

Submitted by billnbdadmin on Wed, 06/11/2014 - 10:57

Product type:

- [Audio Transformers](#)

Price:

75.970

Secondary Impedance Ohms Split Windings SER:

200

Primary Impedance Ohms:

30000.000

Secondary Impedance Ohms Split Windings PAR:

50.000

Power Watts 1 KHz and higher:

0.330

Power Watts 300 Hz and higher:

0.330

Primary Unbalanced DC Current ma:

0.600

Primary DC Resistance Ohms:

2400.000

Secondary DC Resistance Ohms SER CONN:

19.000

Secondary DC Resistance Ohms PAR CONN:

4.750

Turns Ratio Prim/Sec SEC SER CONN:

12.2:1

Turns Ratio Prim/Sec SEC PAR CONN:

24.5:1

Power Watts 75 Hz and higher:

0.030

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [75 Hz](#)

Series:

- [Series 82000](#)

Primary Impedance Ohms_text:

30000

Frequency Response Range:

- [75 Hz to 30 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

99.50

Maximum Voltage at 300 Hz (Volt):

99.50

Maximum Voltage at 75 Hz (Volt):

30.00