

83050

Submitted by billnbdadmin on Wed, 06/11/2014 - 12:26

Product type:

- [Audio Transformers](#)

Price:

50.190

Secondary Impedance Ohms Split Windings SER:

12 ct

Primary Impedance Ohms:

150.000

Secondary Impedance Ohms Split Windings PAR:

3.000

Power Watts 1 KHz and higher:

2.000

Power Watts 300 Hz and higher:

1.500

Primary Unbalanced DC Current ma:

8.000

Primary DC Resistance Ohms:

12.000

Secondary DC Resistance Ohms SER CONN:

1.320

Secondary DC Resistance Ohms PAR CONN:

0.330

Turns Ratio Prim/Sec SEC SER CONN:

3.54:1

Turns Ratio Prim/Sec SEC PAR CONN:

7.08:1

Power Watts 50 Hz and higher:

0.030

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [50 Hz](#)

Series:

- [Series 83000](#)

Primary Impedance Ohms_text:

150 ct

Frequency Response Range:

- [50 Hz to 30 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

17.32

Maximum Voltage at 300 Hz (Volt):

15.00

Maximum Voltage at 50 Hz (Volt):

2.12

Custom Link:

13233