

71015

Submitted by billnbdadmin on Fri, 07/19/2013 - 10:33

Product type:

- [Audio Transformers](#)

Price:

48.440

Secondary Impedance Ohms Split Windings SER:

32 ct

Primary Impedance Ohms:

32.000

Secondary Impedance Ohms Split Windings PAR:

8.000

Power Watts 1 KHz and higher:

0.400

Power Watts 400 Hz and higher:

0.075

Primary Unbalanced DC Current ma:

17.600

Primary DC Resistance Ohms:

3.500

Secondary DC Resistance Ohms SER CONN:

4.200

Secondary DC Resistance Ohms PAR CONN:

1.050

Turns Ratio Prim/Sec SEC SER CONN:

1:01

Turns Ratio Prim/Sec SEC PAR CONN:

2:01

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)

Series:

- [Series 71000 and 81000](#)

Primary Impedance Ohms_text:

32 ct

Frequency Response Range:

- [400 Hz to 100 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

3.58

Maximum Voltage at 400 Hz (Volt):

1.55

Custom Link:

13353