71240

Submitted by billnbdadmin on Fri, 07/19/2013 - 10:33

Product type:

- Audio Transformers

Price:

48.440

Secondary Impedance Ohms Split Windings SER:

12.8 ct

Primary Impedance Ohms:

800.000

Secondary Impedance Ohms Split Windings PAR:

3.200

Power Watts 1 KHz and higher:

0.400

Power Watts 400 Hz and higher:

0.075

Primary Unbalanced DC Current ma:

3.500

Primary DC Resistance Ohms:

80.000

Secondary DC Resistance Ohms SER CONN:

1.500

Secondary DC Resistance Ohms PAR CONN:

0.380

Turns Ratio Prim/Sec SEC SER CONN:

7.9:1

Turns Ratio Prim/Sec SEC PAR CONN:

15.8:1

Product Sub-type:

- Surface Mount Gull Lead Square

Terminals:

- Surface Mount

Frequency:

- 1 KHz
- 400 Hz

Series:

- Series 71000 and 81000

Primary Impedance Ohms_text:

800 ct

Frequency Response Range:

- 400 Hz to 100 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

17.89

Maximum Voltage at 400 Hz (Volt):

7.75

Custom Link:

13353