

**71275**

Submitted by billnbdadmin on Fri, 07/19/2013 - 10:33

**Product type:**

- [Audio Transformers](#)

**Price:**

48.440

**Secondary Impedance Ohms Split Windings SER:**

12.8 ct

**Primary Impedance Ohms:**

1060.000

**Secondary Impedance Ohms Split Windings PAR:**

3.200

**Power Watts 1 KHz and higher:**

0.400

**Power Watts 400 Hz and higher:**

0.075

**Primary Unbalanced DC Current ma:**

3.100

**Primary DC Resistance Ohms:**

106.000

**Secondary DC Resistance Ohms SER CONN:**

1.500

**Secondary DC Resistance Ohms PAR CONN:**

0.380

**Turns Ratio Prim/Sec SEC SER CONN:**

9.1:1

**Turns Ratio Prim/Sec SEC PAR CONN:**

18.2:1

**Product Sub-type:**

- [Surface Mount Gull Lead Square](#)

**Terminals:**

- [Surface Mount](#)

## Frequency:

- [1 KHz](#)
- [400 Hz](#)

## Series:

- [Series 71000 and 81000](#)

## Primary Impedance Ohms\_text:

1060 ct

## Frequency Response Range:

- [400 Hz to 100 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

20.59

## Maximum Voltage at 400 Hz (Volt):

8.92

## Custom Link:

13353