

71615

Submitted by billnbdadmin on Fri, 07/19/2013 - 10:33

Product type:

- [Audio Transformers](#)

Price:

63.220

Secondary Impedance Ohms Split Windings SER:

10,000 ct

Primary Impedance Ohms:

30000.000

Secondary Impedance Ohms Split Windings PAR:

2500.000

Power Watts 1 KHz and higher:

0.083

Power Watts 400 Hz and higher:

0.075

Primary Unbalanced DC Current ma:

0.580

Primary DC Resistance Ohms:

3000.000

Secondary DC Resistance Ohms SER CONN:

1200.000

Secondary DC Resistance Ohms PAR CONN:

300.000

Turns Ratio Prim/Sec SEC SER CONN:

1.73:1

Turns Ratio Prim/Sec SEC PAR CONN:

3.46:1

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)

Series:

- [Series 71000 and 81000](#)

Primary Impedance Ohms_text:

30,000 ct

Frequency Response Range:

- [400 Hz to 100 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

49.90

Maximum Voltage at 400 Hz (Volt):

47.43

Custom Link:

13353