76225

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:30

Product type:

- Audio Transformers

Price:

50.320

Secondary Impedance Ohms Split Windings SER:

32 ct

Primary Impedance Ohms:

80.000

Secondary Impedance Ohms Split Windings PAR:

8.000

Power Watts 1 KHz and higher:

0.600

Power Watts 400 Hz and higher:

0.400

Power Watts 300 Hz and higher:

0.300

Primary Unbalanced DC Current ma:

15.000

Primary DC Resistance Ohms:

7.500

Secondary DC Resistance Ohms SER CONN:

4.300

Secondary DC Resistance Ohms PAR CONN:

1.130

Turns Ratio Prim/Sec SEC SER CONN:

1.58:1

Turns Ratio Prim/Sec SEC PAR CONN:

3.16:1

Product Sub-type:

- Surface Mount Gull Lead Square

Terminals:

- Surface Mount

Frequency:

- 1 KHz
- 400 Hz
- 300 Hz

Series:

- Series 76000

Primary Impedance Ohms_text:

80 ct

Frequency Response Range:

- 300 Hz to 75 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

6.93

Maximum Voltage at 400 Hz (Volt):

5.66

Maximum Voltage at 300 Hz (Volt):

4.90

Custom Link:

13354