

76235

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:30

Product type:

- [Audio Transformers](#)

Price:

50.320

Secondary Impedance Ohms Split Windings SER:

12.8 ct

Primary Impedance Ohms:

120.000

Secondary Impedance Ohms Split Windings PAR:

3.200

Power Watts 1 KHz and higher:

0.600

Power Watts 400 Hz and higher:

0.400

Power Watts 300 Hz and higher:

0.300

Primary Unbalanced DC Current ma:

12.000

Primary DC Resistance Ohms:

9.300

Secondary DC Resistance Ohms SER CONN:

2.200

Secondary DC Resistance Ohms PAR CONN:

0.550

Turns Ratio Prim/Sec SEC SER CONN:

3.06:1

Turns Ratio Prim/Sec SEC PAR CONN:

6.12:1

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [300 Hz](#)

Series:

- [Series 76000](#)

Primary Impedance Ohms_text:

120 ct

Frequency Response Range:

- [300 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

8.49

Maximum Voltage at 400 Hz (Volt):

6.93

Maximum Voltage at 300 Hz (Volt):

6.00

Custom Link:

13354