

76515

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:30

Product type:

- [Audio Transformers](#)

Price:

50.320

Secondary Impedance Ohms Split Windings SER:

1000 ct

Primary Impedance Ohms:

4000.000

Secondary Impedance Ohms Split Windings PAR:

250.000

Power Watts 1 KHz and higher:

0.600

Power Watts 400 Hz and higher:

0.400

Power Watts 300 Hz and higher:

0.300

Primary Unbalanced DC Current ma:

2.000

Primary DC Resistance Ohms:

350.000

Secondary DC Resistance Ohms SER CONN:

115.000

Secondary DC Resistance Ohms PAR CONN:

29.000

Turns Ratio Prim/Sec SEC SER CONN:

2:01

Turns Ratio Prim/Sec SEC PAR CONN:

4:01

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [300 Hz](#)

Series:

- [Series 76000](#)

Primary Impedance Ohms_text:

4000 ct

Frequency Response Range:

- [300 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

48.99

Maximum Voltage at 400 Hz (Volt):

40.00

Maximum Voltage at 300 Hz (Volt):

34.64

Custom Link:

13354