76540

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:30

Product type:

- Audio Transformers

Price:

55.830

Secondary Impedance Ohms Split Windings SER:

100 ct

Primary Impedance Ohms:

7500.000

Secondary Impedance Ohms Split Windings PAR:

25.000

Power Watts 1 KHz and higher:

0.600

Power Watts 400 Hz and higher:

0.400

Power Watts 300 Hz and higher:

0.300

Primary Unbalanced DC Current ma:

1.500

Primary DC Resistance Ohms:

600.000

Secondary DC Resistance Ohms SER CONN:

12.000

Secondary DC Resistance Ohms PAR CONN:

3.000

Turns Ratio Prim/Sec SEC SER CONN:

8.66:1

Turns Ratio Prim/Sec SEC PAR CONN:

17.3:1

Product Sub-type:

- Surface Mount Gull Lead Square

Terminals:

- Surface Mount

Frequency:

- 1 KHz
- 400 Hz
- 300 Hz

Series:

- Series 76000

Primary Impedance Ohms_text:

7500 ct

Frequency Response Range:

- 300 Hz to 75 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

67.08

Maximum Voltage at 400 Hz (Volt):

54.77

Maximum Voltage at 300 Hz (Volt):

47.43

Custom Link:

13354