

76630

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:30

Product type:

- [Audio Transformers](#)

Price:

55.830

Secondary Impedance Ohms Split Windings SER:

5000 ct

Primary Impedance Ohms:

10000.000

Secondary Impedance Ohms Split Windings PAR:

1250.000

Power Watts 1 KHz and higher:

0.600

Power Watts 400 Hz and higher:

0.400

Power Watts 300 Hz and higher:

0.300

Primary Unbalanced DC Current ma:

1.400

Primary DC Resistance Ohms:

850.000

Secondary DC Resistance Ohms SER CONN:

630.000

Secondary DC Resistance Ohms PAR CONN:

158.000

Turns Ratio Prim/Sec SEC SER CONN:

1.41:1

Turns Ratio Prim/Sec SEC PAR CONN:

2.83:1

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [300 Hz](#)

Series:

- [Series 76000](#)

Primary Impedance Ohms_text:

10,000 ct

Frequency Response Range:

- [300 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

77.46

Maximum Voltage at 400 Hz (Volt):

63.25

Maximum Voltage at 300 Hz (Volt):

54.77

Custom Link:

13354