

77210

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:59

Product type:

- [Audio Transformers](#)

Price:

50.320

Secondary Impedance Ohms Split Windings SER:

32 ct

Primary Impedance Ohms:

32.000

Secondary Impedance Ohms Split Windings PAR:

8.000

Power Watts 1 KHz and higher:

1.000

Power Watts 400 Hz and higher:

0.750

Primary Unbalanced DC Current ma:

18.000

Primary DC Resistance Ohms:

2.700

Secondary DC Resistance Ohms SER CONN:

3.700

Secondary DC Resistance Ohms PAR CONN:

0.930

Turns Ratio Prim/Sec SEC SER CONN:

1:01

Turns Ratio Prim/Sec SEC PAR CONN:

2:01

Power Watts 150 Hz and higher:

0.110

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series 77000](#)

Primary Impedance Ohms_text:

32 ct

Frequency Response Range:

- [150 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

5.66

Maximum Voltage at 400 Hz (Volt):

4.90

Maximum Voltage at 150 Hz (Volt):

1.88

Power Watts 150 Hz and higher Tag:

- [0.110](#)

Custom Link:

13231