

77218

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:59

Product type:

- [Audio Transformers](#)

Price:

50.320

Secondary Impedance Ohms Split Windings SER:

16 ct

Primary Impedance Ohms:

48.000

Secondary Impedance Ohms Split Windings PAR:

4.000

Power Watts 1 KHz and higher:

1.000

Power Watts 400 Hz and higher:

0.750

Primary Unbalanced DC Current ma:

13.000

Primary DC Resistance Ohms:

4.500

Secondary DC Resistance Ohms SER CONN:

2.400

Secondary DC Resistance Ohms PAR CONN:

0.600

Turns Ratio Prim/Sec SEC SER CONN:

1.73:1

Turns Ratio Prim/Sec SEC PAR CONN:

3.46:1

Power Watts 150 Hz and higher:

0.110

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series 77000](#)

Primary Impedance Ohms_text:

48 ct

Frequency Response Range:

- [150 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

6.93

Maximum Voltage at 400 Hz (Volt):

6.00

Maximum Voltage at 150 Hz (Volt):

2.30

Power Watts 150 Hz and higher Tag:

- [0.110](#)

Custom Link:

13231