

**77240**

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:59

**Product type:**

- [Audio Transformers](#)

**Price:**

50.320

**Secondary Impedance Ohms Split Windings SER:**

60 ct

**Primary Impedance Ohms:**

120.000

**Secondary Impedance Ohms Split Windings PAR:**

15.000

**Power Watts 1 KHz and higher:**

1.000

**Power Watts 400 Hz and higher:**

0.750

**Primary Unbalanced DC Current ma:**

9.000

**Primary DC Resistance Ohms:**

10.800

**Secondary DC Resistance Ohms SER CONN:**

8.500

**Secondary DC Resistance Ohms PAR CONN:**

2.200

**Turns Ratio Prim/Sec SEC SER CONN:**

1.41:1

**Turns Ratio Prim/Sec SEC PAR CONN:**

2.83:1

**Power Watts 150 Hz and higher:**

0.110

**Product Sub-type:**

- [Surface Mount Gull Lead Square](#)

## Terminals:

- [Surface Mount](#)

## Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

## Series:

- [Series 77000](#)

## Primary Impedance Ohms\_text:

120 ct

## Frequency Response Range:

- [150 Hz to 75 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

10.95

## Maximum Voltage at 400 Hz (Volt):

9.49

## **Maximum Voltage at 150 Hz (Volt):**

3.63

## **Power Watts 150 Hz and higher Tag:**

- [0.110](#)

## **Custom Link:**

13231