77435

Submitted by billnbdadmin on Mon, 07/22/2013 - 11:59

Product type:

- Audio Transformers

Price:

50.320

Secondary Impedance Ohms Split Windings SER:

12.8 ct

Primary Impedance Ohms:

1060.000

Secondary Impedance Ohms Split Windings PAR:

3.200

Power Watts 1 KHz and higher:

1.000

Power Watts 400 Hz and higher:

0.750

Primary Unbalanced DC Current ma:

3.000

Primary DC Resistance Ohms:

115.000

Secondary DC Resistance Ohms SER CONN:

1.750

Secondary DC Resistance Ohms PAR CONN:

0.440

Turns Ratio Prim/Sec SEC SER CONN:

9.1:1

Turns Ratio Prim/Sec SEC PAR CONN:

18.2:1

Power Watts 150 Hz and higher:

0.110

Product Sub-type:

- Surface Mount Gull Lead Square

Terminals:

- Surface Mount

Frequency:

- 1 KHz
- 400 Hz
- 150 Hz

Series:

- Series 77000

Primary Impedance Ohms_text:

1060 ct

Frequency Response Range:

- 150 Hz to 75 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

32.56

Maximum Voltage at 400 Hz (Volt):

28.20

Maximum Voltage at 150 Hz (Volt):

10.80

Power Watts 150 Hz and higher Tag:

- 0.110

Custom Link:

13231