

78005

Submitted by billnbdadmin on Mon, 07/22/2013 - 12:37

Product type:

- [Audio Transformers](#)

Price:

65.650

Secondary Impedance Ohms Split Windings SER:

8 ct

Primary Impedance Ohms:

20.000

Secondary Impedance Ohms Split Windings PAR:

2.000

Power Watts 1 KHz and higher:

0.400

Power Watts 300 Hz and higher:

0.050

Primary Unbalanced DC Current ma:

22.300

Primary DC Resistance Ohms:

1.660

Secondary DC Resistance Ohms SER CONN:

0.930

Secondary DC Resistance Ohms PAR CONN:

0.230

Turns Ratio Prim/Sec SEC SER CONN:

1.58:1

Turns Ratio Prim/Sec SEC PAR CONN:

3.16:1

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)

Series:

- [Series 78000](#)

Primary Impedance Ohms_text:

20 ct

Frequency Response Range:

- [300 Hz to 200 KHz](#)

Frequency Response:

2

Maximum Voltage at 1 KHz (Volt):

2.83

Maximum Voltage at 300 Hz (Volt):

1.00

Custom Link:

13351