

78155

Submitted by billnbdadmin on Mon, 07/22/2013 - 12:37

Product type:

- [Audio Transformers](#)

Price:

76.520

Secondary Impedance Ohms Split Windings SER:

4000 ct

Primary Impedance Ohms:

400.000

Secondary Impedance Ohms Split Windings PAR:

1000.000

Power Watts 1 KHz and higher:

0.400

Power Watts 300 Hz and higher:

0.050

Primary Unbalanced DC Current ma:

5.000

Primary DC Resistance Ohms:

33.300

Secondary DC Resistance Ohms SER CONN:

466.600

Secondary DC Resistance Ohms PAR CONN:

116.600

Turns Ratio Prim/Sec SEC SER CONN:

01:03.2

Turns Ratio Prim/Sec SEC PAR CONN:

01:01.6

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)

Series:

- [Series 78000](#)

Primary Impedance Ohms_text:

400 ct

Frequency Response Range:

- [300 Hz to 200 KHz](#)

Frequency Response:

2

Maximum Voltage at 1 KHz (Volt):

12.65

Maximum Voltage at 300 Hz (Volt):

4.47

Custom Link:

13351