

78275

Submitted by billnbdadmin on Mon, 07/22/2013 - 12:37

Product type:

- [Audio Transformers](#)

Price:

78.540

Secondary Impedance Ohms Split Windings SER:

12.8 ct

Primary Impedance Ohms:

1060.000

Secondary Impedance Ohms Split Windings PAR:

3.200

Power Watts 1 KHz and higher:

0.400

Power Watts 300 Hz and higher:

0.050

Primary Unbalanced DC Current ma:

3.100

Primary DC Resistance Ohms:

88.300

Secondary DC Resistance Ohms SER CONN:

1.490

Secondary DC Resistance Ohms PAR CONN:

0.370

Turns Ratio Prim/Sec SEC SER CONN:

9.1:1

Turns Ratio Prim/Sec SEC PAR CONN:

18.2:1

Product Sub-type:

- [Surface Mount Gull Lead Square](#)

Terminals:

- [Surface Mount](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)

Series:

- [Series 78000](#)

Primary Impedance Ohms_text:

1060 ct

Frequency Response Range:

- [300 Hz to 200 KHz](#)

Frequency Response:

2

Maximum Voltage at 1 KHz (Volt):

20.59

Maximum Voltage at 300 Hz (Volt):

7.28

Custom Link:

13351