70060

Submitted by billnbdadmin on Mon, 07/22/2013 - 17:15

Product type:

- Audio Transformers

Price:

71.370

Secondary Impedance Ohms Split Windings SER:

120 ct

Primary Impedance Ohms:

120.000

Secondary Impedance Ohms Split Windings PAR:

30.000

Power Watts 1 KHz and higher:

0.125

Power Watts 400 Hz and higher:

0.020

Primary Unbalanced DC Current ma:

3.300

Primary DC Resistance Ohms:

13.200

Secondary DC Resistance Ohms SER CONN:

16.000

Secondary DC Resistance Ohms PAR CONN:

4.000

Turns Ratio Prim/Sec SEC SER CONN:

1:01

Turns Ratio Prim/Sec SEC PAR CONN:

2:01

Product Sub-type:

- Surface Mount Gull Lead Square

Terminals:

- Surface Mount

Frequency:

- 1 KHz
- 400 Hz

Series:

- Series 70000 and 80000

Primary Impedance Ohms_text:

120 ct

Frequency Response Range:

- 400 Hz to 250 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

3.87

Maximum Voltage at 400 Hz (Volt):

1.55

Custom Link:

13352