

# 70510

Submitted by billnbdadmin on Mon, 07/22/2013 - 17:15

## **Product type:**

- [Audio Transformers](#)

## **Price:**

77.300

## **Secondary Impedance Ohms Split Windings SER:**

400 ct

## **Primary Impedance Ohms:**

15000.000

## **Secondary Impedance Ohms Split Windings PAR:**

100.000

## **Power Watts 1 KHz and higher:**

0.100

## **Power Watts 400 Hz and higher:**

0.015

**Primary Unbalanced DC Current ma:**

0.350

**Primary DC Resistance Ohms:**

1420.000

**Secondary DC Resistance Ohms SER CONN:**

43.000

**Secondary DC Resistance Ohms PAR CONN:**

10.750

**Turns Ratio Prim/Sec SEC SER CONN:**

6.12:1

**Turns Ratio Prim/Sec SEC PAR CONN:**

12.24:1

**Product Sub-type:**

- [Surface Mount Gull Lead Square](#)

**Terminals:**

- [Surface Mount](#)

## Frequency:

- [1 KHz](#)
- [400 Hz](#)

## Series:

- [Series 70000 and 80000](#)

## Primary Impedance Ohms\_text:

15,000 ct

## Frequency Response Range:

- [400 Hz to 250 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

38.73

## Maximum Voltage at 400 Hz (Volt):

15.00

## Custom Link:

13352