T-22144

Submitted by billnbdadmin on Tue, 07/23/2013 - 12:51

Product type:

- Audio Transformers

Price:

66.050

Secondary Impedance Ohms Split Windings SER:

16 ct

Primary Impedance Ohms:

500.000

Secondary Impedance Ohms Split Windings PAR:

4.000

Power Watts 1 KHz and higher:

3.000

Power Watts 300 Hz and higher:

2.000

Primary Unbalanced DC Current ma:

4.500

Primary DC Resistance Ohms:

40.000

Secondary DC Resistance Ohms SER CONN:

1.600

Secondary DC Resistance Ohms PAR CONN:

0.400

Turns Ratio Prim/Sec SEC SER CONN:

5.6:1

Turns Ratio Prim/Sec SEC PAR CONN:

11.2:1

Power Watts 20 Hz and higher:

0.006

Product Sub-type:

- Thru Hole

Frequency:

- 1 KHz
- 300 Hz
- 20 Hz

Series:

- Series T

Primary Impedance Ohms_text:

500 ct

Frequency Response Range:

- 20 Hz to 25 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

38.73

Maximum Voltage at 300 Hz (Volt):

31.62

Maximum Voltage at 20 Hz (Volt):

1.73

Custom Link:

13253