

T-22215

Submitted by billnbdadmin on Tue, 07/23/2013 - 12:51

Product type:

- [Audio Transformers](#)

Price:

66.050

Secondary Impedance Ohms Split Windings SER:

600 ct

Primary Impedance Ohms:

900.000

Secondary Impedance Ohms Split Windings PAR:

150.000

Power Watts 1 KHz and higher:

3.000

Power Watts 300 Hz and higher:

2.000

Primary Unbalanced DC Current ma:

3.000

Primary DC Resistance Ohms:

72.000

Secondary DC Resistance Ohms SER CONN:

60.000

Secondary DC Resistance Ohms PAR CONN:

15.000

Turns Ratio Prim/Sec SEC SER CONN:

1.22:1

Turns Ratio Prim/Sec SEC PAR CONN:

2.45:1

Power Watts 20 Hz and higher:

0.006

Product Sub-type:

- [Thru Hole](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [20 Hz](#)

Series:

- [Series T](#)

Primary Impedance Ohms_text:

900 ct

Frequency Response Range:

- [20 Hz to 25 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

51.96

Maximum Voltage at 300 Hz (Volt):

42.43

Maximum Voltage at 20 Hz (Volt):

2.32

Custom Link:

13253