

# T-22312

Submitted by billnbdadmin on Tue, 07/23/2013 - 12:51

## **Product type:**

- [Audio Transformers](#)

## **Price:**

66.050

## **Secondary Impedance Ohms Split Windings SER:**

16 ct

## **Primary Impedance Ohms:**

4000.000

## **Secondary Impedance Ohms Split Windings PAR:**

4.000

## **Power Watts 1 KHz and higher:**

2.500

## **Power Watts 300 Hz and higher:**

2.000

**Primary Unbalanced DC Current ma:**

1.600

**Primary DC Resistance Ohms:**

320.000

**Secondary DC Resistance Ohms SER CONN:**

1.600

**Secondary DC Resistance Ohms PAR CONN:**

0.400

**Turns Ratio Prim/Sec SEC SER CONN:**

15.8:1

**Turns Ratio Prim/Sec SEC PAR CONN:**

31.6:1

**Power Watts 20 Hz and higher:**

0.006

**Product Sub-type:**

- [Thru Hole](#)

## Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [20 Hz](#)

## Series:

- [Series T](#)

## Primary Impedance Ohms\_text:

4000 ct

## Frequency Response Range:

- [20 Hz to 25 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

100.00

## Maximum Voltage at 300 Hz (Volt):

89.44

## Maximum Voltage at 20 Hz (Volt):

4.90

## Custom Link:

13253