

T-22535

Submitted by billnbdadmin on Tue, 07/23/2013 - 12:51

Product type:

- [Audio Transformers](#)

Price:

81.620

Secondary Impedance Ohms Split Windings SER:

5000 ct

Primary Impedance Ohms:

30000.000

Secondary Impedance Ohms Split Windings PAR:

1250.000

Power Watts 1 KHz and higher:

0.330

Power Watts 300 Hz and higher:

0.330

Primary Unbalanced DC Current ma:

0.600

Primary DC Resistance Ohms:

2400.000

Secondary DC Resistance Ohms SER CONN:

500.000

Secondary DC Resistance Ohms PAR CONN:

125.000

Turns Ratio Prim/Sec SEC SER CONN:

2.45:1

Turns Ratio Prim/Sec SEC PAR CONN:

4.9:1

Power Watts 20 Hz and higher:

0.006

Product Sub-type:

- [Thru Hole](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [20 Hz](#)

Series:

- [Series T](#)

Primary Impedance Ohms_text:

30,000 ct

Frequency Response Range:

- [20 Hz to 25 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

99.50

Maximum Voltage at 300 Hz (Volt):

99.50

Maximum Voltage at 20 Hz (Volt):

13.42

Custom Link:

13253