

T-22585

Submitted by billnbdadmin on Tue, 07/23/2013 - 12:54

Product type:

- [Audio Transformers](#)

Price:

105.400

Secondary Impedance Ohms Split Windings SER:

50 ct

Primary Impedance Ohms:

62500.000

Secondary Impedance Ohms Split Windings PAR:

12.500

Power Watts 1 KHz and higher:

0.160

Power Watts 300 Hz and higher:

0.160

Primary Unbalanced DC Current ma:

0.400

Primary DC Resistance Ohms:

5000.000

Secondary DC Resistance Ohms SER CONN:

5.000

Secondary DC Resistance Ohms PAR CONN:

1.250

Turns Ratio Prim/Sec SEC SER CONN:

35.4:1

Turns Ratio Prim/Sec SEC PAR CONN:

70.7:1

Power Watts 20 Hz and higher:

0.006

Product Sub-type:

- [Thru Hole](#)

Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [20 Hz](#)

Series:

- [Series T](#)

Primary Impedance Ohms_text:

62,500 ct

Frequency Response Range:

- [20 Hz to 25 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

100.00

Maximum Voltage at 300 Hz (Volt):

100.00

Maximum Voltage at 20 Hz (Volt):

19.36

Custom Link:

13253