

## **S-21135**

Submitted by billnbdadmin on Tue, 07/23/2013 - 14:35

### **Product type:**

- [Audio Transformers](#)

### **Price:**

60.160

### **Secondary Impedance Ohms Split Windings SER:**

2000 ct

### **Primary Impedance Ohms:**

400.000

### **Secondary Impedance Ohms Split Windings PAR:**

500.000

### **Power Watts 1 KHz and higher:**

2.000

### **Power Watts 300 Hz and higher:**

1.500

**Primary Unbalanced DC Current ma:**

5.000

**Primary DC Resistance Ohms:**

32.000

**Secondary DC Resistance Ohms SER CONN:**

220.000

**Secondary DC Resistance Ohms PAR CONN:**

55.000

**Turns Ratio Prim/Sec SEC SER CONN:**

01:02.2

**Turns Ratio Prim/Sec SEC PAR CONN:**

01:01.1

**Power Watts 50 Hz and higher:**

0.030

**Product Sub-type:**

- [Thru Hole](#)

## Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [50 Hz](#)

## Series:

- [Series S](#)

## Primary Impedance Ohms\_text:

400 ct

## Frequency Response Range:

- [75 Hz to 30 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

28.28

## Maximum Voltage at 300 Hz (Volt):

24.49

## Maximum Voltage at 50 Hz (Volt):

3.46

## Custom Link:

13252