S-21140

Submitted by billnbdadmin on Tue, 07/23/2013 - 14:35

Product type:

- Audio Transformers

Price:

60.160

Secondary Impedance Ohms Split Windings SER:

4000 ct

Primary Impedance Ohms:

400.000

Secondary Impedance Ohms Split Windings PAR:

1000.000

Power Watts 1 KHz and higher:

2.000

Power Watts 300 Hz and higher:

1.500

Primary Unbalanced DC Current ma:

5.000

Primary DC Resistance Ohms:

32.000

Secondary DC Resistance Ohms SER CONN:

440.000

Secondary DC Resistance Ohms PAR CONN:

110.000

Turns Ratio Prim/Sec SEC SER CONN:

01:03.2

Turns Ratio Prim/Sec SEC PAR CONN:

01:01.6

Power Watts 50 Hz and higher:

0.030

Product Sub-type:

- Thru Hole

Frequency:

- 1 KHz
- 300 Hz
- 50 Hz

Series:

- Series S

Primary Impedance Ohms_text:

400 ct

Frequency Response Range:

- 75 Hz to 30 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

28.28

Maximum Voltage at 300 Hz (Volt):

24.49

Maximum Voltage at 50 Hz (Volt):

3.46

Custom Link:

13252