S-21210

Submitted by billnbdadmin on Tue, 07/23/2013 - 14:35

Product type:

- Audio Transformers

Price:

60.160

Secondary Impedance Ohms Split Windings SER:

800 ct

Primary Impedance Ohms:

800.000

Secondary Impedance Ohms Split Windings PAR:

200.000

Power Watts 1 KHz and higher:

2.000

Power Watts 300 Hz and higher:

1.500

Primary Unbalanced DC Current ma:

3.500

Primary DC Resistance Ohms:

64.000

Secondary DC Resistance Ohms SER CONN:

88.000

Secondary DC Resistance Ohms PAR CONN:

22.000

Turns Ratio Prim/Sec SEC SER CONN:

1:01

Turns Ratio Prim/Sec SEC PAR CONN:

2:01

Power Watts 50 Hz and higher:

0.030

Product Sub-type:

- Thru Hole

Frequency:

- 1 KHz
- 300 Hz
- 50 Hz

Series:

- Series S

Primary Impedance Ohms_text:

800 ct

Frequency Response Range:

- 75 Hz to 30 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

40.00

Maximum Voltage at 300 Hz (Volt):

34.64

Maximum Voltage at 50 Hz (Volt):

4.90

Custom Link:

13252