S-21312

Submitted by billnbdadmin on Tue, 07/23/2013 - 14:35

Product type:

- Audio Transformers

Price:

62.550

Secondary Impedance Ohms Split Windings SER:

16 ct

Primary Impedance Ohms:

4000.000

Secondary Impedance Ohms Split Windings PAR:

4.000

Power Watts 1 KHz and higher:

2.000

Power Watts 300 Hz and higher:

1.500

Primary Unbalanced DC Current ma:

1.600

Primary DC Resistance Ohms:

320.000

Secondary DC Resistance Ohms SER CONN:

1.760

Secondary DC Resistance Ohms PAR CONN:

0.440

Turns Ratio Prim/Sec SEC SER CONN:

15.8:1

Turns Ratio Prim/Sec SEC PAR CONN:

31.6:1

Power Watts 50 Hz and higher:

0.030

Product Sub-type:

- Thru Hole

Frequency:

- 1 KHz
- 300 Hz
- 50 Hz

Series:

- Series S

Primary Impedance Ohms_text:

4000 ct

Frequency Response Range:

- 75 Hz to 30 KHz

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

89.44

Maximum Voltage at 300 Hz (Volt):

77.46

Maximum Voltage at 50 Hz (Volt):

10.95

Custom Link:

13252