

## **S-21545**

Submitted by billnbdadmin on Tue, 07/23/2013 - 14:35

### **Product type:**

- [Audio Transformers](#)

### **Price:**

79.740

### **Secondary Impedance Ohms Split Windings SER:**

30,000 ct

### **Primary Impedance Ohms:**

30000.000

### **Secondary Impedance Ohms Split Windings PAR:**

0.000

### **Power Watts 1 KHz and higher:**

0.330

### **Power Watts 300 Hz and higher:**

0.330

**Primary Unbalanced DC Current ma:**

0.600

**Primary DC Resistance Ohms:**

2400.000

**Secondary DC Resistance Ohms SER CONN:**

3300.000

**Secondary DC Resistance Ohms PAR CONN:**

0.000

**Turns Ratio Prim/Sec SEC SER CONN:**

1:01

**Turns Ratio Prim/Sec SEC PAR CONN:**

-

**Power Watts 50 Hz and higher:**

0.030

**Product Sub-type:**

- [Thru Hole](#)

## Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [50 Hz](#)

## Series:

- [Series S](#)

## Primary Impedance Ohms\_text:

\*30,000 ct

## Frequency Response Range:

- [75 Hz to 30 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

99.50

## Maximum Voltage at 300 Hz (Volt):

99.50

## Maximum Voltage at 50 Hz (Volt):

30.00

## Custom Link:

13252