

## **R-20455**

Submitted by billnbdadmin on Tue, 07/23/2013 - 16:43

### **Product type:**

- [Audio Transformers](#)

### **Price:**

82.130

### **Secondary Impedance Ohms Split Windings SER:**

600 ct

### **Primary Impedance Ohms:**

15000.000

### **Secondary Impedance Ohms Split Windings PAR:**

150.000

### **Power Watts 1 KHz and higher:**

0.660

### **Power Watts 300 Hz and higher:**

0.660

**Primary Unbalanced DC Current ma:**

0.800

**Primary DC Resistance Ohms:**

1200.000

**Secondary DC Resistance Ohms SER CONN:**

57.000

**Secondary DC Resistance Ohms PAR CONN:**

14.300

**Turns Ratio Prim/Sec SEC SER CONN:**

5:01

**Turns Ratio Prim/Sec SEC PAR CONN:**

10:01

**Power Watts 75 Hz and higher:**

0.030

**Product Sub-type:**

- [Thru Hole](#)

## Frequency:

- [1 KHz](#)
- [300 Hz](#)
- [75 Hz](#)

## Series:

- [Series R](#)

## Primary Impedance Ohms\_text:

15,000 ct

## Frequency Response Range:

- [75 Hz to 30 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

99.50

## Maximum Voltage at 300 Hz (Volt):

99.50

## Maximum Voltage at 75 Hz (Volt):

21.21

**Custom Link:**

13251