

N-6228

Submitted by billnbdadmin on Wed, 07/24/2013 - 09:44

Product type:

- [Audio Transformers](#)

Price:

54.840

Secondary Impedance Ohms Split Windings SER:

40 ct

Primary Impedance Ohms:

100.000

Secondary Impedance Ohms Split Windings PAR:

10.000

Power Watts 1 KHz and higher:

1.000

Power Watts 400 Hz and higher:

0.750

Primary Unbalanced DC Current ma:

10.000

Primary DC Resistance Ohms:

9.700

Secondary DC Resistance Ohms SER CONN:

5.600

Secondary DC Resistance Ohms PAR CONN:

1.400

Turns Ratio Prim/Sec SEC SER CONN:

1.58:1

Turns Ratio Prim/Sec SEC PAR CONN:

3.16:1

Power Watts 150 Hz and higher:

0.110

Mil Spec Part Number:

M27/358-008

Product Sub-type:

- [Thru Hole](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series N and K](#)

Primary Impedance Ohms_text:

100 ct

Frequency Response Range:

- [150 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

10.00

Maximum Voltage at 400 Hz (Volt):

8.66

Maximum Voltage at 150 Hz (Volt):

3.32

Power Watts 150 Hz and higher Tag:

- [0.110](#)

Custom Link:

13250