

N-6835

Submitted by billnbdadmin on Wed, 07/24/2013 - 09:44

Product type:

- [Audio Transformers](#)

Price:

96.070

Secondary Impedance Ohms Split Windings SER:

20,000 ct

Primary Impedance Ohms:

200000.000

Secondary Impedance Ohms Split Windings PAR:

5000.000

Power Watts 1 KHz and higher:

0.050

Power Watts 400 Hz and higher:

0.050

Primary Unbalanced DC Current ma:

0.200

Primary DC Resistance Ohms:

17340.000

Secondary DC Resistance Ohms SER CONN:

3000.000

Secondary DC Resistance Ohms PAR CONN:

750.000

Turns Ratio Prim/Sec SEC SER CONN:

3.16:1

Turns Ratio Prim/Sec SEC PAR CONN:

6.32:1

Power Watts 150 Hz and higher:

0.050

Product Sub-type:

- [Thru Hole](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series N and K](#)

Primary Impedance Ohms_text:

200,000 ct

Frequency Response Range:

- [150 Hz to 20 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

100.00

Maximum Voltage at 400 Hz (Volt):

100.00

Maximum Voltage at 150 Hz (Volt):

100.00

Power Watts 150 Hz and higher Tag:

- [0.05](#)

Custom Link:

13250