

## **K-7405**

Submitted by billnbdadmin on Wed, 07/24/2013 - 09:44

### **Product type:**

- [Audio Transformers](#)

### **Price:**

52.970

### **Secondary Impedance Ohms Split Windings SER:**

48 ct

### **Primary Impedance Ohms:**

800.000

### **Secondary Impedance Ohms Split Windings PAR:**

12.000

### **Power Watts 1 KHz and higher:**

1.000

### **Power Watts 400 Hz and higher:**

0.750

**Primary Unbalanced DC Current ma:**

3.500

**Primary DC Resistance Ohms:**

74.000

**Secondary DC Resistance Ohms SER CONN:**

6.000

**Secondary DC Resistance Ohms PAR CONN:**

1.500

**Turns Ratio Prim/Sec SEC SER CONN:**

4.08:1

**Turns Ratio Prim/Sec SEC PAR CONN:**

8.16:1

**Power Watts 150 Hz and higher:**

0.110

**Product Sub-type:**

- [Insulated Leads](#)

## Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

## Series:

- [Series N and K](#)

## Primary Impedance Ohms\_text:

800 ct

## Frequency Response Range:

- [150 Hz to 75 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

28.28

## Maximum Voltage at 400 Hz (Volt):

24.49

## Maximum Voltage at 150 Hz (Volt):

9.38

## **Power Watts 150 Hz and higher Tag:**

- [0.110](#)

## **Custom Link:**

13250