

K-7514**

Submitted by billnbdadmin on Wed, 07/24/2013 - 09:44

Product type:

- [Audio Transformers](#)

Price:

52.970

Secondary Impedance Ohms Split Windings SER:

600 ct

Primary Impedance Ohms:

4000.000

Secondary Impedance Ohms Split Windings PAR:

150.000

Power Watts 1 KHz and higher:

1.000

Power Watts 400 Hz and higher:

0.750

Primary Unbalanced DC Current ma:

1.500

Primary DC Resistance Ohms:

395.000

Secondary DC Resistance Ohms SER CONN:

66.000

Secondary DC Resistance Ohms PAR CONN:

17.000

Turns Ratio Prim/Sec SEC SER CONN:

2.58:1

Turns Ratio Prim/Sec SEC PAR CONN:

5.16:1

Power Watts 150 Hz and higher:

0.110

Product Sub-type:

- [Insulated Leads](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series N and K](#)

Primary Impedance Ohms_text:

4000 ct

Frequency Response Range:

- [150 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

63.25

Maximum Voltage at 400 Hz (Volt):

54.77

Maximum Voltage at 150 Hz (Volt):

20.98

Power Watts 150 Hz and higher Tag:

- [0.110](#)

Custom Link:

13250