

K-7660

Submitted by billnbdadmin on Wed, 07/24/2013 - 09:44

Product type:

- [Audio Transformers](#)

Price:

59.080

Secondary Impedance Ohms Split Windings SER:

10,000 ct

Primary Impedance Ohms:

15000.000

Secondary Impedance Ohms Split Windings PAR:

2500.000

Power Watts 1 KHz and higher:

0.660

Power Watts 400 Hz and higher:

0.660

Primary Unbalanced DC Current ma:

0.800

Primary DC Resistance Ohms:

1165.000

Secondary DC Resistance Ohms SER CONN:

1050.000

Secondary DC Resistance Ohms PAR CONN:

263.000

Turns Ratio Prim/Sec SEC SER CONN:

1.22:1

Turns Ratio Prim/Sec SEC PAR CONN:

2.45:1

Power Watts 150 Hz and higher:

0.110

Product Sub-type:

- [Insulated Leads](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series N and K](#)

Primary Impedance Ohms_text:

15,000 ct

Frequency Response Range:

- [150 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

99.50

Maximum Voltage at 400 Hz (Volt):

99.50

Maximum Voltage at 150 Hz (Volt):

40.62

Power Watts 150 Hz and higher Tag:

- [0.110](#)

Custom Link:

13250