

K-7795

Submitted by billnbdadmin on Wed, 07/24/2013 - 09:44

Product type:

- [Audio Transformers](#)

Price:

91.830

Secondary Impedance Ohms Split Windings SER:

15,000 ct

Primary Impedance Ohms:

95000.000

Secondary Impedance Ohms Split Windings PAR:

3750.000

Power Watts 1 KHz and higher:

0.100

Power Watts 400 Hz and higher:

0.100

Primary Unbalanced DC Current ma:

0.300

Primary DC Resistance Ohms:

9550.000

Secondary DC Resistance Ohms SER CONN:

1635.000

Secondary DC Resistance Ohms PAR CONN:

410.000

Turns Ratio Prim/Sec SEC SER CONN:

2.5:1

Turns Ratio Prim/Sec SEC PAR CONN:

5:01

Power Watts 150 Hz and higher:

0.100

Product Sub-type:

- [Insulated Leads](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series N and K](#)

Primary Impedance Ohms_text:

95,000 ct

Frequency Response Range:

- [150 Hz to 20 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

97.47

Maximum Voltage at 400 Hz (Volt):

97.47

Maximum Voltage at 150 Hz (Volt):

97.47

Power Watts 150 Hz and higher Tag:

- [0.100](#)

Custom Link:

13250