

K-7820

Submitted by billnbdadmin on Wed, 07/24/2013 - 09:44

Product type:

- [Audio Transformers](#)

Price:

93.240

Secondary Impedance Ohms Split Windings SER:

82 ct

Primary Impedance Ohms:

135000.000

Secondary Impedance Ohms Split Windings PAR:

20.500

Power Watts 1 KHz and higher:

0.074

Power Watts 400 Hz and higher:

0.074

Primary Unbalanced DC Current ma:

0.250

Primary DC Resistance Ohms:

13700.000

Secondary DC Resistance Ohms SER CONN:

9.500

Secondary DC Resistance Ohms PAR CONN:

2.400

Turns Ratio Prim/Sec SEC SER CONN:

40.6:1

Turns Ratio Prim/Sec SEC PAR CONN:

81.2:1

Power Watts 150 Hz and higher:

0.074

Product Sub-type:

- [Insulated Leads](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [150 Hz](#)

Series:

- [Series N and K](#)

Primary Impedance Ohms_text:

135,000 ct

Frequency Response Range:

- [150 Hz to 20 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

99.95

Maximum Voltage at 400 Hz (Volt):

99.95

Maximum Voltage at 150 Hz (Volt):

99.95

Power Watts 150 Hz and higher Tag:

- [0.074](#)

Custom Link:

13250