

P-9765

Submitted by billnbdadmin on Wed, 07/24/2013 - 10:51

Product type:

- [Audio Transformers](#)

Price:

68.410

Secondary Impedance Ohms Split Windings SER:

20,000 ct

Primary Impedance Ohms:

40000.000

Secondary Impedance Ohms Split Windings PAR:

5000.000

Power Watts 1 KHz and higher:

0.250

Power Watts 400 Hz and higher:

0.250

Power Watts 300 Hz and higher:

0.250

Primary Unbalanced DC Current ma:

0.700

Primary DC Resistance Ohms:

3400.000

Secondary DC Resistance Ohms SER CONN:

2700.000

Secondary DC Resistance Ohms PAR CONN:

675.000

Turns Ratio Prim/Sec SEC SER CONN:

1.41:1

Turns Ratio Prim/Sec SEC PAR CONN:

2.83:1

Product Sub-type:

- [Insulated Leads](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [300 Hz](#)

Series:

- [Series L and P](#)

Primary Impedance Ohms_text:

40,000 ct

Frequency Response Range:

- [300 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

100.00

Maximum Voltage at 400 Hz (Volt):

100.00

Maximum Voltage at 300 Hz (Volt):

100.00

Custom Link:

13249