

P-9805

Submitted by billnbdadmin on Wed, 07/24/2013 - 10:51

Product type:

- [Audio Transformers](#)

Price:

88.530

Secondary Impedance Ohms Split Windings SER:

100 ct

Primary Impedance Ohms:

100000.000

Secondary Impedance Ohms Split Windings PAR:

25.000

Power Watts 1 KHz and higher:

0.100

Power Watts 400 Hz and higher:

0.100

Power Watts 300 Hz and higher:

0.100

Primary Unbalanced DC Current ma:

0.400

Primary DC Resistance Ohms:

8750.000

Secondary DC Resistance Ohms SER CONN:

15.000

Secondary DC Resistance Ohms PAR CONN:

3.800

Turns Ratio Prim/Sec SEC SER CONN:

31.6:1

Turns Ratio Prim/Sec SEC PAR CONN:

63.2:1

Product Sub-type:

- [Insulated Leads](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)
- [300 Hz](#)

Series:

- [Series L and P](#)

Primary Impedance Ohms_text:

100,000 ct

Frequency Response Range:

- [300 Hz to 75 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

100.00

Maximum Voltage at 400 Hz (Volt):

100.00

Maximum Voltage at 300 Hz (Volt):

100.00

Custom Link:

13249