

F-28385

Submitted by billnbdadmin on Wed, 07/24/2013 - 11:39

Product type:

- [Audio Transformers](#)

Price:

72.870

Secondary Impedance Ohms Split Windings SER:

500 ct

Primary Impedance Ohms:

5000.000

Secondary Impedance Ohms Split Windings PAR:

125.000

Power Watts 1 KHz and higher:

0.125

Power Watts 400 Hz and higher:

0.020

Primary Unbalanced DC Current ma:

0.500

Primary DC Resistance Ohms:

540.000

Secondary DC Resistance Ohms SER CONN:

65.000

Secondary DC Resistance Ohms PAR CONN:

16.250

Turns Ratio Prim/Sec SEC SER CONN:

3.16:1

Turns Ratio Prim/Sec SEC PAR CONN:

6.32:1

Product Sub-type:

- [Thru Hole](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)

Series:

- [Series F and G](#)

Primary Impedance Ohms_text:

5000 ct

Frequency Response Range:

- [400 Hz to 250 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

25.00

Maximum Voltage at 400 Hz (Volt):

10.00

Custom Link:

13246