

## **F-28440**

Submitted by billnbdadmin on Wed, 07/24/2013 - 11:39

### **Product type:**

- [Audio Transformers](#)

### **Price:**

80.180

### **Secondary Impedance Ohms Split Windings SER:**

12.8 ct

### **Primary Impedance Ohms:**

10000.000

### **Secondary Impedance Ohms Split Windings PAR:**

3.200

### **Power Watts 1 KHz and higher:**

0.125

### **Power Watts 400 Hz and higher:**

0.020

**Primary Unbalanced DC Current ma:**

0.360

**Primary DC Resistance Ohms:**

1200.000

**Secondary DC Resistance Ohms SER CONN:**

1.600

**Secondary DC Resistance Ohms PAR CONN:**

0.400

**Turns Ratio Prim/Sec SEC SER CONN:**

28:01:00

**Turns Ratio Prim/Sec SEC PAR CONN:**

56:01:00

**Product Sub-type:**

- [Thru Hole](#)

**Frequency:**

- [1 KHz](#)
- [400 Hz](#)

## Series:

- [Series F and G](#)

## Primary Impedance Ohms\_text:

10,000 ct

## Frequency Response Range:

- [400 Hz to 250 KHz](#)

## Frequency Response:

3

## Maximum Voltage at 1 KHz (Volt):

35.36

## Maximum Voltage at 400 Hz (Volt):

14.14

## Custom Link:

13246