# <u>G-29015</u>

Submitted by billnbdadmin on Wed, 07/24/2013 - 11:39

## **Product type:**

Audio Transformers

# Price:

59.470

## Secondary Impedance Ohms Split Windings SER:

32 ct

## **Primary Impedance Ohms:**

32.000

## Secondary Impedance Ohms Split Windings PAR:

8.000

#### Power Watts 1 KHz and higher:

0.125

#### Power Watts 400 Hz and higher:

0.020

### **Primary Unbalanced DC Current ma:**

6.500

## **Primary DC Resistance Ohms:**

3.520

## Secondary DC Resistance Ohms SER CONN:

4.320

# Secondary DC Resistance Ohms PAR CONN:

1.080

## Turns Ratio Prim/Sec SEC SER CONN:

1:01

## Turns Ratio Prim/Sec SEC PAR CONN:

2:01

## **Product Sub-type:**

• Insulated Leads

# Frequency:

- <u>1 KHz</u>
- <u>400 Hz</u>

## Series:

• Series F and G

## **Primary Impedance Ohms\_text:**

32 ct

## **Frequency Response Range:**

• <u>400 Hz to 250 KHz</u>

# **Frequency Response:**

3

## Maximum Voltage at 1 KHz (Volt):

2.00

# Maximum Voltage at 400 Hz (Volt):

0.80

## **Custom Link:**

13246