

G-29095

Submitted by billnbdadmin on Wed, 07/24/2013 - 11:39

Product type:

- [Audio Transformers](#)

Price:

64.520

Secondary Impedance Ohms Split Windings SER:

12 ct

Primary Impedance Ohms:

300.000

Secondary Impedance Ohms Split Windings PAR:

3.000

Power Watts 1 KHz and higher:

0.125

Power Watts 400 Hz and higher:

0.020

Primary Unbalanced DC Current ma:

2.000

Primary DC Resistance Ohms:

33.000

Secondary DC Resistance Ohms SER CONN:

1.560

Secondary DC Resistance Ohms PAR CONN:

0.390

Turns Ratio Prim/Sec SEC SER CONN:

5:01

Turns Ratio Prim/Sec SEC PAR CONN:

10:01

Product Sub-type:

- [Insulated Leads](#)

Frequency:

- [1 KHz](#)
- [400 Hz](#)

Series:

- [Series F and G](#)

Primary Impedance Ohms_text:

300 ct

Frequency Response Range:

- [400 Hz to 250 KHz](#)

Frequency Response:

3

Maximum Voltage at 1 KHz (Volt):

6.12

Maximum Voltage at 400 Hz (Volt):

2.45

Custom Link:

13246