



NOTES

- a. ALL DIMENSIONS ARE IN INCHES, [] = MM
- b. RECOMMENDED TORQUE FOR MOUNTING SCREWS: 6-9 INCH-LBS
- c. EXTERNAL CAPACITOR REQUIRED ACROSS TERMINALS 4 AND 5

PIN	FUNCTION	PIN DIAMETER
1	AC IN	.040 [1.016]
2	AC IN	.040 [1.016]
3	AC IN	.040 [1.016]
4	+380 V BUS	.040 [1.016]
5	-V BUS	.040 [1.016]
6	-V OUT	.080 [2.032]
7	+V OUT	.080 [2.032]

BOTTOM VIEW

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PICO ELECTRONICS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PICO ELECTRONICS INC. IS PROHIBITED

DRAWN	P.PALUCH	<div><div>PICO</div><div>Electronics</div></div> <div>143 Sparks Ave Village of Pelham, NY 10803</div>				
CHECKED	H. VIDAURRE					
QA		SERIES AC3				
MFG						
APPROVED		SIZE C				
REVISION DATE	06/06/2023					
		SCALE NTS		DWG NO		REV 1
		www.picoelectronics.com				