

Series QP

50W Isolated Regulated High Power DC-DC Converter



PRODUCT OVERVIEW

The QP series are isolated DC-DC converters with a wide selection of input voltage ranges from 4.5V to 475V while maintaining tight output regulation, low ripple and noise. These modules have trim capability, shutdown and internal reference voltage. Protections include input over/undervoltage, output short-circuit, output overvoltage and over temperature. For increased reliability, the feedback loop does not use an optocoupler.

The 2.5" x 1.55" x 0.5" case size has threaded inserts to mount securely for high vibration and shock applications. Conduction cooling is available through the baseplate or compatible heat sink.



FEATURES

- 4.75V to 475V input range models
- 5 to 500V output models
- Up to 50W output
- Input/output isolation
- Protected against input over/undervoltage, output short-circuit overcurrent (HiQP) and over temperature
- Does not use optocoupler in feedback loop
- External bias for capacitor charging applications (QP)
- Load Share Parallel operation (HiQP)
- Industrial temperature option -40°C (HiQP)
- Military temperature option -55°C (HiQP)
- Input LC filter for soft start and low reflected current ripple (HiQP)

Contact Pico for part number of available options:

- Expanded operating temp: -55°C to +85°C (QP)
- Select screening per MIL-STD-883:
 - Stabilization Bake
 - Temperature Cycle
 - Burn-In
- Special Input Voltage, Output Voltage, Isolation Voltage or Output Power

Hi	QP	24	-M
INPUT VOLTAGE RANGE	SERIES NAME	NOM. OUTPUT VOLTAGE	TEMPERATURE
6 = 4.75 - 9V 12 = 9 - 18V 24 = 18 - 36V 48 = 36 - 72V	QP	5 = 5V 12 = 12V 15 = 15V 24 = 24V 48 = 48V 100 = 100V 200 = 200V 300 = 300V 400 = 400V 500 = 500V	Blank = 0°C to +85°C
Hi = 125 - 475V	QP	24 = 24V 48 = 48V 100 = 100V 200 = 200V	Blank = 0°C to +70°C -I = -40°C to +95°C -M = -55°C to +95°C

MODEL LIST

Pico Part Number	Output Voltage [VDC]	Output Current		Output Power [W]	Efficiency ⁽²⁾ [%] typ.	Line Regulation [%] max	Load Regulation 10-100% ⁽¹⁾ [%] max	Output Ripple @ 1MHz BW [mVp-p] max
		Min. [mA]	Max. [mA]					
6QP5.0	5	400	4000	20	73	4	2	50
6QP12	12	167	1667	20	82	2	1.5	40
6QP15	15	167	1667	25	82	2	1.5	40
6QP24	24	104	1042	25	81	1.5	1	20
6QP28	28	89	893	25	81	1.5	1	20
6QP48	48	52	521	25	80	2	1.5	30
6QP100	100	25	250	25	82	3	2	20
6QP200	200	13	125	25	77	3	2	150
6QP300	300	7	67 ⁽³⁾	20 ⁽³⁾	80	2.5	2	100
6QP400	400	5	50 ⁽³⁾	20 ⁽³⁾	79	2.5	2	200
6QP500	500	4	40 ⁽³⁾	20 ⁽³⁾	76	2	1.5	200
12QP5.0	5	800	8000	40	78	3	3	50
12QP12	12	333	3333	40	85	1.5	2	40
12QP15	15	333	3333	50	85	1.5	2	40
12QP24	24	208	2083	50	85	1	1.5	20
12QP28	28	179	1786	50	85	1	1.5	20
12QP48	48	104	1042	50	85	1	1.5	30
12QP100	100	50	500	50	86	1	1.5	20
12QP200	200	25	250	50	85	1.5	2	150
12QP300	300	13	133 ⁽⁴⁾	40 ⁽⁴⁾	87	1	1	100
12QP400	400	10	100 ⁽⁴⁾	40 ⁽⁴⁾	87	1	1	200
12QP500	500	8	80 ⁽⁴⁾	40 ⁽⁴⁾	86	1	1	200
24QP5.0	5	800	8000	40	79	3	2	50
24QP12	12	333	3333	40	88	1	1.5	40
24QP15	15	333	3333	50	88	1	1.5	40
24QP24	24	208	2083	50	87	1	1	20
24QP28	28	179	1786	50	87	1	1	20
24QP48	48	104	1042	50	87	1	1	30
24QP100	100	50	500	50	88	1	1	20
24QP200	200	25	250	50	87	1	1.5	150
24QP300	300	13	133	40	90	0.5	1	100
24QP400	400	10	100	40	89	0.5	0.5	200
24QP500	500	8	80	40	89	1	1	200

Note 1: Maintain minimum 10% of rated load to prevent a voltage surge.

Note 2: Tested at nominal input voltage and full output load.

Note 3: Below 5.5V input, derate linearly 7.5W per input voltage.

Note 4: Below 10.5V input, derate linearly 6.7W per input voltage.

MODEL LIST								
Pico Part Number	Output Voltage [VDC]	Output Current		Output Power [W]	Efficiency ⁽²⁾ [%] typ.	Line Regulation [%] max	Load Regulation 10-100% ⁽⁵⁾ [%] max	Output Ripple @ 1MHz BW [mVp-p] max
		Min. [mA]	Max. [mA]					
48QP5.0	5	800	8000	40	81	2	2	30
48QP12	12	417	4167	50	83	1	1	20
48QP15	15	333	3333	50	84	1	1	30
48QP24	24	208	2083	50	88	1	1	20
48QP28	28	179	1786	50	88	1	1	20
48QP48	48	104	1042	50	89	1	1	30
48QP100	100	50	500	50	89	1	1	50
48QP200	200	25	250	50	89	1	1.5	250
48QP300	300	13	133	40	90	0.5	1	200
48QP400	400	10	100	40	87	0.5	1	200
48QP500	500	8	80	40	89	1	1.5	200
HiQP24	24	104	2083	50	86	0.25	1.25	350
HiQP24-I								
HiQP24-M								
HiQP28	28	89	1786	50	86	0.25	1.25	375
HiQP28-I								
HiQP28-M								
HiQP48	48	52	1042	50	85	0.25	1.75	400
HiQP48-I								
HiQP48-M								
HiQP100	100	25	500	50	88	0.3	1.6	600
HiQP100-I								
HiQP100-M								
HiQP200	200	13	250	50	89	0.1	1.5	750
HiQP200-I								
HiQP200-M								

Note 5: For 6QP, 12QP, 24QP & 48QP models, maintain minimum 10% of rated load to prevent a voltage surge. For HiQP models, maintain minimum 5% of rated load to prevent >2% voltage overshoot.

SPECIFICATIONS (Nominal V_{IN} , Full Load, $T_A = +25^\circ\text{C}$, 1 hour warm up unless otherwise specified)**INPUT**

Parameter	Condition	Min.	Typ.	Max.	Units	
Input Voltage Range	6V input models	4.5	6	9	VDC	
	12V input models	9	12	18		
	24V input models	18	24	36		
	48V input models	36	48	72		
	HiQP models	125	250	475		
Input Filter	HiQP models	LC filter				
Input Current	HiQP models	Short-circuit condition	-	-	8	mA
		Shutdown mode	-	-	0.5	
Input Reflected Ripple Current	HiQP models	20MHz, Full Load	-	10	-	%

OUTPUT

Parameter	Condition	Min.	Typ.	Max.	Units	
Output Voltage Tolerance	Nominal V_{IN} , Full Load	QP models	-	-	0.5	%
		HiQP models	-	-	1	

ENVIRONMENTAL

Parameter	Condition	Min.	Typ.	Max.	Units	
Operating Temperature Range	Baseplate	QP models	0	-	+85	°C
		HiQP models	0	-	+70	
		HiQP -I models	-40	-	+95	
		HiQP -M models	-55	-	+95	
Storage Temperature Range		-55	-	+125	°C	
Cooling	Conduction through baseplate					

GENERAL

Parameter	Condition	Min.	Typ.	Max.	Units	
Operating Frequency	QP models, Fixed frequency	≤200V output models	-	200	-	kHz
		≥300V output models	-	150	-	
	HiQP models, Variable frequency	80	-	110		
Isolation Voltage	Input to output	4242	-	-	VDC	
	Input to baseplate	2121	-	-		
	Output to baseplate	1000	-	-		
Insulation Resistance		100	-	-	MΩ	
Size	L x W x H	2.5 x 1.55 x 0.5 (76.2 x 39.37 x 12.7)			inches (mm)	
Weight		-	75	-	grams	
Case	Aluminum baseplate and Glass Reinforced Polymer					
Potting	Vacuum Impregnated Epoxy					
Tube Packaging (W x H x L)	2.595 x 1.135 x 20 (65.913 x 28.829 x 101.6)				inches (mm)	

SPECIFICATIONS (Nominal V_{IN} , Full Load, $T_A = +25^{\circ}\text{C}$, 1 hour warm up unless otherwise specified)

PROTECTIONS & FEATURES

Parameter	Condition		Min.	Typ.	Max.	Units	
Short circuit or Overload	Hiccup mode, self-recovery		-	130	-	%	
Overtemperature	Baseplate, self-recovery	All other models	Shutdown	-	95	-	°C
			Restart	-	50	-	
		HiQP -I & -M models	Shutdown	-	110	-	
			Restart	-	100	-	
Output Overvoltage	Zener diode clamp		-	120	-	%	
Input Under Voltage	Non-latched shutdown Self-recovery	6V input models	Shutdown	-	3.6	-	VDC
			Restart	-	4.25	-	
		12V input models	Shutdown	-	7.1	-	
			Restart	-	7.6	-	
		24V input models	Shutdown	-	14.6	-	
			Restart	-	15.6	-	
		48V input models	Shutdown	-	31.2	-	
			Restart	-	31.8	-	
HiQP models	Shutdown	-	60	-			
	Restart	-	107	-			
Input Over Voltage	Non-latched shutdown Self-recovery	6V input models	Shutdown	-	11	-	VDC
			Restart	-	10.8	-	
		12V input models	Shutdown	-	20	-	
			Restart	-	19.5	-	
		24V input models	Shutdown	-	41	-	
			Restart	-	40	-	
		48V input models	Shutdown	-	82	-	
			Restart	-	81.5	-	
HiQP models	Shutdown	-	560	-			
	Restart	-	500	-			
Shutdown (SHDN) ⁽¹⁾	Non-latched shutdown, Self-recovery		-	-	0.4	VDC	
Output Voltage Trim (TRIM)	QP models		-5	0	-	%	
	HiQP models		-15	0	15		
Voltage Reference (VREF)	Voltage	QP models	2.8	3	3.2	VDC	
		HiQP models	2.94	3	3.06		
	Current		0	-	10	mA	
External Bias (EX. B) ⁽²⁾	QP models		Voltage	17	-	20	VDC
			Current	-	20	-	mA
Load Share (LDSH) ⁽³⁾	HiQP models		Connect directly to the load share pin of Pico's HiQP converters.				

Note 1: For 6QP, 12QP, 24QP & 48QP models, the voltage of the open shutdown pin is equal to the input voltage. All external components must be rated to at least the input voltage.

Note 2: The external bias pin should be used in an application which requires a large startup current such as capacitor charging. This will disable and prevent the overload or short-circuit protections. After the output has reached 90-95% nominal value, internal bias should be used so normal operations and protections can be restored. External bias should not be connected when not in use.

Note 3: The load share pin allows units to operate the outputs in parallel to share load, increase total power or allow for N+1 redundancy.

SPECIFICATIONS (Nominal V_{IN} , Full Load, $T_A = +25^\circ\text{C}$, 1 hour warm up unless otherwise specified)

DESIGNED TO MEET

Test	Referenced Standard	Description
Vibration	MIL-STD-202	Method 204, Vibration, High Frequency, Condition D
Shock	MIL-STD-202	Method 213, Shock (Specified Pulse), Condition I
Humidity	MIL-STD-202	Method 106, Moisture Resistance
Altitude	MIL-STD-202	Method 105, Barometric Pressure (Reduced), Condition D

OPTIONS AVAILABLE - CONTACT PICO FOR PART NUMBER

Parameter	Referenced Standard	Description
Stabilization Bake	MIL-STD-883	Referenced Method 1008 Non-operating maximum storage temperature for 24 hours
Temperature Cycle	MIL-STD-883	Referenced Method 1010 Non-operating at temperature extremes, 15 mins/temp, 10 cycles
Burn-In	MIL-STD-883	Referenced Method 1015 Max operating temperature for 160 hours
Expanded Operating Temperature Range		-40°C to +85°C (Series QP)

THERMAL RESISTANCE

$$P_{OUT} = \frac{T_C - T_A}{T_{RCA} \times (1 / \eta - 1)}$$

P_{OUT} = Output Power in Watts

η = Efficiency

T_C = Case temperature in °C

T_A = Ambient temperature in °C


T_{RCA} = Thermal resistance of case to air in °C / W

Thermal resistance of case (T_{RCA})

Air Flow	Baseplate only	QCH Heat Sink	Units
Free Air	9.6	5.6	°C / W
200 LFM	5.1	3.0	
400 LFM	3.7	2.2	
600 LFM	3.1	1.8	
800 LFM	2.6	1.5	
1000 LFM	2.2	1.3	


DERATING GRAPHS (Nominal V_{IN} , Full Load, Efficiency @ Full Load)

QP Models with Max. Output Power = 40W
& Efficiency at full load = 89%




P/N HiQP200-I & HiQP200-M

Max. Output Power = 50W
& Efficiency at full load = 89%





TYPICAL CONNECTION CIRCUIT

TRIM DOWN - 6QP, 12QP, 24QP & 48QP MODELS





Resistance	Open	374	162	91	33	kΩ typ.
Trim Down	0	-1	-2	-3	-5	$V_{OUT} \%$

TRIM UP & TRIM DOWN - HIQP MODELS




Resistance	Open	1000	470	100	47	10	1	0 (Short)	kΩ typ.
Trim Up	0	0.5	1	4	7	14	16	17	$V_{OUT} \%$
Trim Down	0	-1	-3	-7	-9	-13	-15	-16	

EXTERNAL BIAS - SERIES QP



TYPICAL CONNECTION CIRCUIT


LOAD SHARE - HIQP MODELS




Note 4: When using Load Share function, -IN terminals must be connected directly.

SHUTDOWN

NON-ISOLATED




ISOLATED



Note 5: The voltage of the open shutdown pin is equal to the input voltage. All external components must be rated to at least the input voltage.


MECHANICAL DRAWINGS



PIN	FUNCTION		PIN DIAMETER
	QP MODELS	HIQP MODELS	
1	-IN		.062 [1.575]
2	SHDN		.040 [1.016]
3	VREF		.040 [1.016]
4	TRIM		.040 [1.016]
5	EX. B	LDSH	.040 [1.016]
6	+IN		.062 [1.575]
7	+OUT		.062 [1.575]
8	-OUT		.062 [1.575]


NOTES

- a. ALL DIMENSIONS ARE IN INCHES, [] = MM
- b. RECOMMENDED TORQUE FOR MOUNTING SCREWS: 3-5 INCH-LBS



MECHANICAL DRAWINGS


QTI - THERMAL INTERFACE



BOTTOM VIEW


Material	Alloy Aluminum Substrate
Thermal Conductivity	1530 BTU-in/hr sq.ft °F
Coefficient of Thermal Expansion, (25-100°C)	13.1 10 ⁻⁶ in-in/°F
Brinell Hardness	23 HB
Endurance Limit	5000 PSI
Standard Thickness	0.002 inches

QCH - HEAT SINK






TOP VIEW

Weight: 51.3 grams typical







MECHANICAL DRAWINGS

HEAT SINK ASSEMBLY



ITEM	QTY	DESCRIPTION
1	1	QCH HEAT SINK
2	1	QTI THERMAL INTERFACE
3	1	QP MODULE
4	1	PCB

TUBE PACKAGING



Pico warrants each product manufactured by us and sold by us or an authorized representative, to be free from defects in material and workmanship. If properly used, it will perform within its applicable specifications for a period of one year after original shipment. Pico's obligation under this guarantee is limited to repairing or replacing our product to the original purchaser. This warranty is in lieu of all other warranties, express or implied and constitutes fulfillment of our obligations to the purchaser. We do not guarantee that the products can be used for a particular purpose other than those solely covered by the product's specifications. Pico must be notified if the product must meet particular certifications and/or standards. We assume no liability, in any event, for consequential damages, for anticipated or lost profits, incidental damages or loss of time or other losses incurred by the purchaser or any third party in connection with products covered by this warranty or otherwise. The purchaser will indemnify and hold Pico harmless for any damages, losses, costs, etc. from usage not within the product's specifications. Pico must be consulted before usage of its products in a nuclear, radioactive or space environment.

We reserve the right to discontinue products without notice, We reserve the right to make modifications to any existing catalog products without notice, at any time, without the obligation to modify units previously sold.